

zapier.georgelambert.org · Markdown indexes

VERAE TIME × ZAPIER

add_numbers

site/docs/modules/verae-activate/creates/add_numbers.md

verae-activate/creates/add_numbers

Package: verae-activate**Source:** packages/verae-activate/creates/add_numbers.js**Lines:** 95

What this module is

Implementation module in `verae-activate`. The tables below are extracted from the source (signatures + JSDoc).

Exports

`key`, `noun`, `display`, `label`, `description`

Types / interfaces / classes

None extracted.

Functions

Name	Parameters	Param types (JSDoc)	Returns	Calls (same file / helpers)
<code>toFiniteNumber</code>	<code>value, name</code>	value: <code>unknown</code> , name: <code>string</code>	<code>number</code>	see Call graph
<code>perform</code>	<code>z, bundle</code>	z: <code>object</code> , bundle: <code>object</code> , bundle.inputData: <code>object</code> , bundle.inputData.number1: <code>string number</code> , bundle.inputData.number2: <code>string number</code> , bundle.authData: <code>object</code>	<code>Promise<{number1: number, number2: number, sum: number, mode: string —>}</code>	see Call graph

What it imports / requires

No imports detected.

Call graph (identifiers invoked)

`number2`, `toFiniteNumber`, `isFinite`, `async`, `replace`, `request`

Each identifier is a call site in this file. Follow the import list to see the defining module; open that module's MD for parameter and return types.

Return values (how to read this)

- HTTP route handlers return Express `res.json(...)` bodies (see route docs).
- Zapier `perform` functions return a **single object** (creates) or an **array** (triggers/searches).
- Pricing functions return integer **cents** on `Quote.totalCents`.