

zapier.georgelambert.org · Markdown indexes

VERAE TIME x ZAPIER

verae-keep

[site/packages/verae-keep/README.md](https://github.com/georgelambert/verae-keep/blob/master/site/packages/verae-keep/README.md)

verae-keep

Host keep-alive for Verae workers. Restarts a unit that crashed **unless** the operator console paused or stopped it.

Forgejo: <https://git.georgelambert.org/marchon/verae-keep>

Two processes:

Process	Port	Job
<code>node src/keep.js</code>	<code>:3860</code>	Probe units, spawn if intent is <code>run</code>
<code>node src/watch.js</code>	<code>:3861</code>	Restart keep if <code>/health</code> fails
<code>scripts/guard.sh</code>	—	Restart watch if watch exits

Intent is `run` | `pause` | `stop`. Sources, newest wins:

1. `POST /intent/:id` (admin / API)
2. `~/verae-fleet-runtime/data/<instance>/intent.json` (fleet writes this on start/pause/stop)
3. live `FLEET_URL/api/status` when set
4. unit `defaultIntent` (`run`)

Pause: leave the process down or `POST /pause`. Stop: `SIGTERM` and do not spawn. Run: spawn if health fails.

NS1 (70.88.205.138)

```
KEEP_UNITS=$HOME/verae-keep/units.ns1.json KEEP_STATE=$HOME/verae-keep/data \
nohup bash scripts/guard.sh >/tmp/verae-keep-guard.out 2>&1 &
```

Or systemd user unit `systemd/verae-keep-guard.service` (`logindctl enable-linger`).

Units: NATS (observe only), job-poller, webhook-deliver, archive-aggregator, archive-worm ×3, tree-node ×3.

API

- GET /health GET /status
- POST /intent/:id {"state":"pause|stop|run"}
- POST /reconcile